

Electrolux Line 5000 Tumble Dryers with Compass Control

Change your point of view.

The new Line 5000 Electrolux Professional dryers offer advanced performance innovation and significant energy savings. Now with easy to use Compass Control, it's perfect for hotels, motels, hospitals, nursing homes, gyms, salons, schools, and other facilities. You'll appreciate the "green" engineering, easy operation, and years of low maintenance.

Features and benefits:

- Axial airflow and tight construction gives low energy consumption
- High productivity - 2 full loads per hour
- Large door opening for easy loading and unloading
- Easy and ergonomic access to the lint screen
- Excellent water evaporation efficiency per kWh
- With Compass Pro program control:
 - Large and clear display with control knob for easy program selection
 - Easy access with user-friendly interface
 - Language selection
 - Drying program packages optimized for Economy, Care and Time
 - Service program for adjustment of parameters
 - USB connection
- Reversing drum (standard) minimizes tangling and wrinkling. Improves dryer efficiency and makes flatwork finishing easier.

Residual Moisture Control:

The Residual Moisture Control (RMC) option is available in all Electrolux single pocket dryers. RMC prevents damage to garments caused by overdrying and reduces lint and wrinkles by automatically stopping the dryer when the exact pre-set moisture level is reached. The amount of residual moisture in the fabric is important for proper finishing. If the load is to be further processed by an ironer, RMC will shut the dryer off while there is still sufficient moisture for the ironer to work effectively. By not overdrying, you'll benefit from longer linen life and significant labor and energy savings.



35, 67, and 83 lb. capacities.

Available in stainless (optional) or wave front panel. Other options include: Stainless steel drum, RMC, Heat recovery system: Heat Recovery Pipes (HRP), fresh air intake, exhaust on top, and more. Contact the Laundrylux Sales Dept. to learn more.

The future of professional laundry is here.

Electrolux is dedicated to providing you with the very best precision-engineered washers, dryers, and flatwork ironers. Production units are certified in accordance with ISO 9001 (Quality) and ISO 14001 (Environmental Management) standards, and products are CE labeled. Take control of your laundry operations with Electrolux Professional Laundry.

For more information, please visit www.laundrylux.com

Main specifications			T5290				T5550				T5675			
Rated capacity, filling factor 1:18	kg/lb		16.1/35.5				30.5/67.2				37.5/82.7			
Rated capacity, filling factor 1:22	kg/lb		13.2/29.1				25/55.1				30.6/67.5			
Drum volume	litre/ft ³		290/10.2				550/19.4				675/23.8			
Drum diameter	mm/inch		680 / 26 3/4				913 / 35 15/16				913 / 35 15/16			
Heating alternatives														
electric	kW		13.5/18				24/32				32/40			
gas	BTU/h (kW)		71 700 (21)				11 2700 (33)				14 3400 (42)			
steam at 87-102 psi	kW		25				46				46			
Consumption data*			13.5 kW	18 kW	Gas	Steam	24 kW	32 kW	Gas	Steam	32 kW	40 kW	Gas	Steam
Total time at 29.1 lbs	min		27	21	20	23	28	23	24	23	28	22	23	26
Energy consumption at 29.1 lbs	kWh		6.32	6.15	7.13	10.29	12.21	12.50	13.05	19.05	15.00	14.62	15.68	23.86
Evaporation	oz/min		8.6	10.7	11.6	10.3	15.9	18.7	18	19	19.2	23.8	22.9	20.7
Energy kWh/gallon water evaporated	kWh/gallon		0.25	0.26	0.28	0.41	0.26	0.26	0.28	0.40	0.26	0.26	0.3	0.4

* At rated capacity 100% cotton load at 50% initial moisture dried to 0%.

Electrical connections			T5290		T5550		T5675	
Heating Voltage								
El.	208-240V 3N AC 60 Hz	kW(A)	10.9-14.4 (45)		20.1-26.4 (80)		26.1-34.4 (110)	
	208-240V 3N AC 60 Hz	kW(A)	14.4-18.9 (60)		26.1-34.4 (110)		26.1-34.4 (110)	
Gas/steam	208-240V 3N AC 60 Hz	kW(A)	0.9 (15)		2.1-2.4 (15)		2.1-2.4 (15)	
	208-240V 1N AC 60 Hz	kW(A)	0.8 (15)		2 (15)		2 (15)	
	120V 1N AC 1N AC 60 Hz	kW(A)	0.9 (15)		1.4 (20)		1.4 (20)	
Steam, gas and air connections								
Steam	ISO 7/1-R		1"		1"		1"	
Steam pressure	psi		14.5-145		14.5-145		14.5-145	
Steam consumption	lb/h		143.3		143.3		143.3	
Condensate	ISO 7/1-R		1"		1"		1"	
Gas	NG/PG		1/2"		1/2"		1/2"	
Gas pressure	Natural gas	psi	0.29		0.29		0.29	
		mbar	20		20		20	
	Propane	psi	0.40-0.54		0.40-0.54		0.40-0.54	
		mbar	28-37		28-37		28-37	
Air outlet	ø mm/inch		200 / 7 7/8		200 / 7 7/8		200 / 7 7/8	
Evacuated air* el 13.5 kW	ft ³ /h		13420		28252		35315	
el 18 kW	ft ³ /h		15892		35315		40612	
steam			22601		42378		45909	
gas			19423		31783		35315	
Pressure drop (el 13.5 kW/el 18 kW)	Max. psi		0.050/0.058		0.029/0.022		0.022/0.029	
(steam/gas)	Max. psi		0.050/0.050		0.022/0.022		0.022/0.022	
Sound levels								
Airborne sound level	dB(A)		<70		<70		<70	
Heat emission								
% of installed power, max			15		15		15	
Shipping data (el/steam/gas)								
	net, kg/lbs		220/485		300/661		340/750	
	crated, kg/lbs		235/518		325/717		375/827	
	boxed, kg/lbs		330/728		435/959		515/1135	
Shipping volume	crated, m ³ /ft ³		1.72/60.7		3.19/113		3.57/126	
Accessories								
Heat recovery pipes			HRP290		HRP290		HRP290	
Fresh air intake			x		x		x	
Dimensions in mm/inch								
Width			710 / 27 15/16		960 / 37 13/16		960 / 37 13/16	
Depth			1155 / 45 1/2		1315 / 51 3/4		1510 / 59 7/16	
Depth			1335 / 52 9/16		1445 / 56 7/8		1640 / 64 9/16	
Height			1675 / 65 15/16		1855 / 73 7/16		1855 / 73 1/16	



Call today for information on the full line of Electrolux Professional washers, dryers, ironers, and low-cost financing & leasing.

Thinking of you

Electrolux

800.381.7222 • www.laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@laundrylux.com

Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@laundrylux.com

Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

Your local independent authorized dealer