

IC44832 (3170 mm/18' 14/16")



IC44832
(3170 mm/18' 14/16")

Easy-to-use electronic control panel, RABC compatible

DIAMMS system

Automatic speed adjustment with moisture sensors to ensure a perfect result.

Pressure roll with tightener springs, prevents wrinkling

Return feed, can be installed close to a wall for maximum space utilisation (LF model)

Labour saving automatic feeding and length-folding device (LF model)

Rear delivery (R model)

Finger guard protection

Provides additional safety for operators.

Durable ironing belts of Nomex withstand temperatures above 200°C

Nickel-plated cylinder prevents rust and improves lifetime.

Rolls diameter, mm/in:	479/18' 14/16"
Ironing width, mm/in:	3170/124' 13/16"
Dimensions (widthxdepthxheight mm):	3835x1070x1270
Speed range, m/min:	1.5 to 9
Automatic Length Folding:	Option
Rear delivery:	Option
Automatic Feeding and Length Folding:	Option
Automatic Feeding and rear delivery:	Option

Maintenance free ceramic gas burner

Increases reliability for gas heated ironers

Air circulation device on electric heated and stainless steel cylinder machines for an homogenous tempera-ture and an increased production**Options**

Multi-layer cylinder Dubixium™ for increased production on electric and gas heated machines
CMIS, Certus Management Information System, connection for traceability according to European Standard EN14065

Electrolux Professional North America, 3225 SW 42nd Street, Fort Lauderdale, Florida 33312 - Toll free: 866.449.4200