



Thinking of you
Electrolux

Electrolux Professional Line 5000

Electrolux Dryers Stack and Single Pocket for OPL

Use up to 25% less gas and dry 12% faster

Built to last, Electrolux dryers are precision-engineered for efficiency, ease of use, and superior drying results. Our dryers are 8-12% larger than competitive models. This allows for even faster drying using less energy, as the linens are allowed to expand, providing more surface area to the heated air. You will appreciate the “green” engineering, cost savings, easy operation, and years of low maintenance.

Features and Benefits:

- Dries 12% faster, saving 25% in gas due to axial airflow, tight construction, and reversing cylinders
- Auto Stop ensures the dryer stops running when the linens are dry. Saves time and energy while preserving linen life.
- Best lint screen in the industry - easiest to clean, ergonomically designed
- Extra large door opening for easy loading and unloading
- Excellent water evaporation efficiency per kWh
- Reversing drums (standard) reduces energy consumption, prevents tangling and wrinkling. Improves efficiency – and laundry dries more quickly
- Fresh air intake adapter acquires air from a location outside the dryer area. Useful when dryers are installed in interior or air-conditioned space.
- 120 volt, single-phase for easy installation

Compass Pro Microprocessor offers:

- Customizable program names
- Large display and one control knob for easy program selection
- More than 20 languages available
- Real-time clock for automatic start and time/date stamp
- Detailed user statistics and programmability
- USB connection in front, easily accessible

Residual Moisture Control

The Residual Moisture Control (RMC) option is available in all Electrolux single pocket dryers. RMC allows for precise control of remaining moisture in the load. This is best for linens that require a small amount of dampness to further process the linens with pressing equipment. By not over-drying, you'll benefit from longer linen life and significant labor and energy savings.



Electrolux OPL Dryers available in 35x35, 50x50, 35, 67, 83, 100 and 135 lb. capacities. Vertical blue wave front panel standard. Stainless available.

Stack dryers and 35, 67 and 83 lb. with Axial Airflow and Compass Pro control. Other options include: Stainless steel drum, RMC, Heat recovery system: Heat Recovery Pipes (HRP), fresh air intake, exhaust on top. Call for more information.

Electrolux energy savings have been measured extensively. Results may vary depending on installation and other conditions.



Designed by experts. Inspired by you.



For more information, please visit www.laundrylux.com

Model	T5300S		T5420S		T5290		T5550		T5675		T4900		T41200	
Capacity (lb/kg)	2 x 35	2 x 15.9	2 x 50	2 x 22.7	35	15.9	67	30.4	83	37.7	100	45.4	135	61.2
Width (in/mm)	31 1/8	790	34 1/4	870	27 15/16	710	37 13/16	960	37 13/16	960	50 13/16	1290	50 13/16	1290
Depth (in/mm)	43 7/8	1115	52 5/8	1336	45 1/2	1155	51 3/4	1315	59 7/16	1510	51	1295	58 7/16	1485
Depth with door open (in/mm)	72 7/16	1840	85 5/8	2175	68 5/16	1735	83 11/16	2125	91 5/16	2320	94 1/2	2400	101 15/16	2590
Height Overall (in/mm)	76 3/8	1940	81 7/8	2078	65 15/16	1675	73 7/16	1855	73 7/16	1855	97 1/16	2465	97 1/16	2465
Height without heating unit (in/mm)	n/a		n/a		n/a		n/a		n/a		77 3/8		77 3/8	
Door opening diameter (in/mm)	22 7/8	580	27	686	22 13/16	580	31 7/8	810	31 7/8	810	37	940	37	940
Cylinder volume (ft ³ /l)	10.6	300	14.6	414	10.2	290	19.4	550	23.8	675	31.8	900	42.4	1200
Crated Weight (lb/kg)	695	315	865	392	518	235	717	325	827	375	1100	500	1166	530
Utility Connections			(2) 8" or (1) 10"											
Exhaust duct diameter (in/mm)	8	200	(2) 203mm or (1) 254mm		8	200	8	250	8	250	12	315	12	315
Gas connection	1/2 NPT		3/4 MNPT		1/2 NPT		1/2 NPT		3/4 NPT		1 NPT		1 NPT	
Steam connection, inlet & condensate	n/a		n/a		1 NPT		1 NPT		1 NPT		1 NPT		1 NPT	
Energy Data														
Gas (Btu/hr)	2 x 71,700		2 x 94,000		71,700		112,700		143,400		219,000		280,000	
Airflow (ft ³ /min / m ³ /hr) (gas heat)	2 x 354	2 x 600	2 x 600	2 x 1020	360 / 610		550 / 940		670 / 1140		1354 / 2300		1765 / 3000	
3000Electric (kW) @ 208-240V/3Ø	2 x 18	n/a	18	30	13.5 or 18		24 or 32		24 or 32		32		72	
Airflow (ft ³ /min / m ³ /hr) (elec. heat)	2 x 354	2 x 600	n/a		325 / 550		550 / 940		670 / 1140		1354 / 2300		1765 / 3000	
Steam (lb/hr / kg/hr) (approximate)	n/a		n/a		80 / 36		118 / 54		150 / 68		315 / 143		315 / 143	
Airflow (ft ³ /min / m ³ /hr) (steam heat)	n/a		n/a		405 / 690		635 / 1080		810 / 1380		1354 / 2300		1765 / 3000	
Electrical Requirements														
Current, gas or steam, 120 V/60Hz (full load/circuit breaker)	2 x 9A / 2 x 15A		2 x 12A / 2 x 15A		7.5A (15A)		12A (20A)		12A (20A)		n/a		n/a	
Current, gas or steam, 208-240 V/60Hz/1Ø (full load/circuit breaker)	2 x 4.5A / 2 x 15A		5.50A / 15A		3.5A (15A)		8.5A (15A)		8.5A (15A)		n/a		n/a	
Current, gas or steam, 208-240 V/60Hz/3Ø (full load/circuit breaker)	n/a		n/a		3.75A (15A)		10A (15A)		10A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	2 x 50 / 2 x 65		n/a		14.4-18.9 (60A)		26.1-34.4 (110A)		26.1-34.4 (110A)		75 / 100 @ 480 Volts		90 / 125 @ 480 VoltsAlternate	
Alternate Voltages														
Alternate voltages available. Contact Laundrylux Sales Department for information.														
Supply Pressures														
Natural Gas (inches H2O/mbar)	6-10/ 15-25		6-12 / 15-30		3.5-10.5 / 9-26		3.5-10.5 / 9-26		3.5-10.5 / 9-26		6-10 / 15 - 25		6-10 / 15 - 25	
Propane (inches H2O/mbar)	10-13 / 25-30		11-13 / 28-33		8-13 / 20-32		8-13 / 20-32		8-13 / 20-32		10-13 / 25-30		10-13 / 25-30	
Steam (psi/bar) (max)	n/a		145 / 10		145 / 10		145 / 10		145 / 10		145 / 10		145 / 10	
Exhaust back pressure (inches H2O/mbar) (max)	1.57	3.9	0.6	1.5	2.2	5.5	2.6	6.48	3	7.5	0.37	1	0.37	1
<p><i>*T4900 and T41200 are Line 4000 and are available with Selecta II Control. Important: Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.</i></p>														



Electrolux Professional Line 5000 The all-in-one business solution for your on-premises laundry.



Dry faster using 25% less gas thanks to tight construction and axial airflow



Longer machine life with support rollers and advanced blower wheel



Reversing Cylinders for time and energy savings. Minimize wrinkling and tangling. Less wear-and-tear on linens.

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

